

DAFTAR PUSTAKA

- [1] K. Mukmin, “PENGARUH ARAH SERAT IJUK TERHADAP KEKUATAN TARIK DAN BENDING MATERIAL KOMPOSIT SERAT IJUK-EPOXY,” UNIVERSITAS NEGERI SEMARANG, 2019.
- [2] A. K. Mishra, “Effect of silica on the thermal properties of LDPE-WF-silica composites,” in *IOP Conference Series: Materials Science and Engineering*, 2012. doi: 10.1088/1757-899X/40/1/012036.
- [3] C. S. Verma, N. K. Sharma, V. M. Chariar, S. Maheshwari, and M. K. Hada, “Comparative study of mechanical properties of bamboo laminae and their laminates with woods and wood based composites,” *Compos. B Eng.*, vol. 60, pp. 523–530, Apr. 2014, doi: 10.1016/j.compositesb.2013.12.061.
- [4] J. I. Preet Singh, V. Dhawan, S. Singh, and K. Jangid, “Study of Effect of Surface Treatment on Mechanical Properties of Natural Fiber Reinforced Composites,” in *Materials Today: Proceedings*, Elsevier Ltd, 2017, pp. 2793–2799. doi: 10.1016/j.matpr.2017.02.158.
- [5] T. D. Ngo, *Composite and Nanocomposite Materials-From Knowledge to Industrial Applications*. London: IntechOpen, 2020.
- [6] The Polyolefin Company (Singapore) Pte Ltd, “Safety Data Sheet,” Dec. 2016.
- [7] I. Wahyudi, “Karakteristik dan Sifat-Sifat Dasar Kayu Jati Unggul Umur 4 dan 5 Tahun Asal Jawa Barat (Characteristics and Basic Properties of 4 and 5 year-old of Superior Teakwoods from West Java),” 2014.
- [8] D. Wahyu Ardaniswari, H. Haritsah, and S. Sembiring, “Karakteristik Termal dan Fungsionalitas Komposit Silika Sekam Padi dengan Aspal,” 2020.
- [9] Degussa, “Aerosil 200_T,” Apr. 04, 2023, *Degussa*. [Online]. Available: <http://www.aerosil.com>
- [10] M. Ufa, N. N, A. F. Ningrum, W. Suwinarti, and R. Amirta, “EFEKTIVITAS PERLAKUAN AWAL ALKALI DAN HIDROTERMAL TERHADAP PROSES DELIGNIFIKASI, POTENSI GULA REDUKSI DAN PRODUKSI ETANOL TEORITIS DARI KAYU *Vernonia amygdalina* Delile,” *ULIN: Jurnal Hutan Tropis*, vol. 6, no. 2, p. 155, Sep. 2022, doi: 10.32522/ujht.v6i2.7438.
- [11] K. T. Leto, “Pemanfaatan Serbuk Gergaji Kayu Jati dan Sengon sebagai Bahan

- Dasar Penghasil Gula Reduksi Kata Kunci,” *Variabel*, vol. 4, no. 1, pp. 1–21, 2021.
- [12] N. K. Jain and M. K. Gupta, “Hybrid teak/sal wood flour reinforced composites: Mechanical, thermal and water absorption properties,” *Mater. Res. Express*, vol. 5, no. 12, Dec. 2018, doi: 10.1088/2053-1591/aae24d.
- [13] L. U. Widodo, F. M. E. Pratama, and S. M. Prastya, “Pemanfaatan Limbah Batang Ubi Kayu dan Plastik Sebagai Bahan Baku Pembuatan Papan Partikel,” *Journal of Research and Technology*, vol. 6, no. 1, pp. 145–154, Jun. 2020.
- [14] American Society for Testing and Materials, “Test Method for Tensile Properties of Plastics,” Dec. 15, 2014, *ASTM International, West Conshohocken, PA*. doi: 10.1520/D0638-14.
- [15] N. Srisawat, M. Nithitanakul, and K. Srikulkit, “Characterizations of Fibers Produced from Polypropylene/ Silica Composite,” 2009.
- [16] X. Zhang, M. Wang, J. Gao, and N. Guo, “Crystallization morphology and space charge property of silica/low density polyethylene composites,” *AIP Adv.*, vol. 10, no. 1, Jan. 2020, doi: 10.1063/1.5135039.
- [17] W. J. Sichina, “DSC as Problem Solving Tool: Measurement of Percent Crystallinity of Thermoplastics,” 2000, *PerkinElmer Instruments, Norwalk*. [Online]. Available: www.perkinelmer.com.
- [18] S. Arif, D. Irawan, and M. Jainudin, “ANALISIS SIFAT MEKANIS PERBANDINGAN CAMPURAN KOMPOSIT SERBUK GERGAJI KAYU JATI DENGAN MATRIK EPOXY UNTUK MATERIAL KAMPAS REM CAKRAM,” *Jurnal Technopreneur (JTech)*, vol. 7, no. 2, pp. 58–63, Nov. 2019, doi: 10.30869/jtech.v7i2.385.
- [19] S. Octavania, E. Maryani, L. S. Hutahaean, U. Prayudie, and Hernawan, “Modifikasi Silika Sebagai Filler Karet Perapat Dengan Coupling Agent HEXAMETHYLDISILAZANE (HDMS) dan METHYLTRIETHOXY SILANE (MTES),” *Jurnal Keramik dan Gelas Indonesia*, vol. 30, no. 2, pp. 103–121, 2021.
- [20] J. Murphy, *Additives for Plastics Handbook 2nd Edition*, 2nd ed., vol. 2. Elsevier, 2001.
- [21] P. N. Khanam and M. A. A. AlMaadeed, “Processing and characterization of polyethylene-based composites,” Apr. 01, 2015, *Taylor and Francis Ltd*. doi: 10.1179/2055035915Y.0000000002.