

DAFTAR PUSTAKA

- [1] M. K. Piamprajakpong, “PROCESS IMPROVEMENT FOR REDUCING THE DEFECT RATE IN CASE STUDY OF LIGHTING EQUIPMENT,” 2016.
- [2] Makrolon, “ISO Datasheet,” 2023.
- [3] S. A. Hafad *dkk.*, “Mechanical properties study of polycarbonate and other thermoplastic polymers,” dalam *Journal of Physics: Conference Series*, IOP Publishing Ltd, Agu 2021. doi: 10.1088/1742-6596/1973/1/012001.
- [4] X. Ouyang *dkk.*, “Biodegradable Microneedle Patch for Transdermal Clopidogrel Delivery,” *Materiale Plastice*, vol. 62, no. 3, hlm. 72–83, 2025, doi: 10.37358/Mat.Plust.1964.
- [5] J. Andrzejewski, W. Gosławska, M. Salamaga, W. Zgoła, dan M. Barczewski, “The Use of the Overmolding Technique for the Preparation of Basalt Fiber (BF)-Based Composite, the Comparative Study of Poly(ethylene terephthalate)/Polycarbonate—PET/PC and Poly(butylene terephthalate)—PBT/PC Blends,” *Polymers (Basel)*., vol. 18, no. 1, Jan 2026, doi: 10.3390/polym18010054.
- [6] H. Liu *dkk.*, “Preparation and Characterization of Polycarbonate-Based Blend System with Favorable Mechanical Properties and 3D Printing Performance,” *Polymers (Basel)*., vol. 15, no. 20, Okt 2023, doi: 10.3390/polym15204066.
- [7] C.-P. Fung, C.-H. Huang, dan J.-L. Doong, “The Study on the Optimization of Injection Molding Process Parameters with Gray Relational Analysis,” *Journal of REINFORCED PLASTICS AND COMPOSITES*, vol. 22, no. 1, 2003, doi: 10.1106/073168403022843.
- [8] S. C. Chen, H. Su, J. J. Mathew, H. Gunawan, C. W. Huang, dan C. Te Feng, “An Investigation to Reduce the Effect of Moisture on Injection-Molded Parts through Optimization of Plasticization Parameters,”

- Applied Sciences (Switzerland)*, vol. 12, no. 3, Feb 2022, doi: 10.3390/app12031410.
- [9] W. D. van Driel dan M. Yazdan Mehr, *Reliability of Organic Compounds in Microelectronics and Optoelectronics: From Physics-of-Failure to Physics-of-Degradation*. Springer International Publishing, 2022. doi: 10.1007/978-3-030-81576-9.
- [10] Y. Choi dan H. Kim, “Degradation behavior of polycarbonate during melt processing with an aqueous solution of sodium hydroxide,” *Polym. Test.*, vol. 128, Nov 2023, doi: 10.1016/j.polymertesting.2023.108236.
- [11] A. Motta, F. P. La Mantia, L. Ascione, dan M. C. Mistretta, “Theoretical study on the decomposition mechanism of bisphenol A polycarbonate induced by the combined effect of humidity and UV irradiation,” *J. Mol. Graph. Model.*, vol. 99, Sep 2020, doi: 10.1016/j.jmglm.2020.107622.
- [12] M. Rides dan C. Allen, “NPL REPORT MAT 3 The use of the melt flow rate method for moisture sensitive materials and an evaluation of the uncertainties in melt flow rate measurement,” 2007. [Daring]. Tersedia pada: www.npl.co.uk
- [13] D. Kyriacos, “Polycarbonates,” dalam *Brydson’s Plastics Materials: Eighth Edition*, Elsevier Inc., 2017, hlm. 457–485. doi: 10.1016/B978-0-323-35824-8.00017-7.
- [14] D. E. Hudgin, *HANDBOOK OF POLY CARBONATE SCIENCE AND TECHNOLOGY*. 2010.
- [15] George. Wypych, *Handbook of polymers*. ChemTec Publishing, 2022.
- [16] J. M. Margolis, “ENGINEERING THERMOPLASTICS; Properties and Applications,” 1985.
- [17] M. Khadliq, C. Budiyanoro, dan H. Sosiati, “KOMPARASI PARAMETER INJEKSI OPTIMUM PADA HDPE RECYCLED DAN VIRGIN MATERIAL,” 2017.
- [18] C. Fernandes, A. J. Pontes, J. C. Viana, dan A. Gaspar-Cunha, “Modeling and Optimization of the Injection-Molding Process: A

- Review,” 1 Maret 2018, *John Wiley and Sons Inc.* doi: 10.1002/adv.21683.
- [19] S. Lubis, E. Siahaan, dan A. P. Manggala, “Minimalisasi Cacat Produk Dengan Optimasi Mekanikal Terhadap Kualitas Produk Pada Proses Plastic Injection Molding,” 2012.
- [20] J. Sreedharan, A. K. Jeevanantham, V. Velumani, dan C. Manimaran, “Behaviour of silver streaks after plating on ABS plastics,” *Journal of Engineering and Applied Sciences*, vol. 13, no. 24, hlm. 10442–10447, 2018, doi: 10.3923/jeasci.2018.10442.10447.
- [21] J. Bilík, A. Náplava, M. Kusý, M. Košík, dan L. Likavčan, “Silver Streaks on Surface of Injected Thermoplastic Parts,” *Research Papers Faculty of Materials Science and Technology Slovak University of Technology*, vol. 22, no. 34, hlm. 21–27, Jun 2014, doi: 10.2478/rput-2014-0023.
- [22] E. Rimawan, M. Kholil, dan S. Fachira, “Analysis quality control of garnish back door license in injection molding process using DMAIC method and VSM method at PT. Suzuki Indomobil Motor,” *Universal Journal of Mechanical Engineering*, vol. 7, no. 6, hlm. 19–31, Des 2019, doi: 10.13189/ujme.2019.071504.
- [23] A. Widodo, “UPAYA MENURUNKAN DEFECT SILVER STREAKS PROSES INJECTION PADA PART LENS REFLECTOR DENGAN MENGGUNAKAN METODE SEVEN TOOLS DI PT SANWA ENGINEERING,” Online, 2023.
- [24] D. V Stan, “Considerations on the Drying of the Raw Material and Consequences on the Quality of the Injected Products,” *Mater. Plast*, vol. 57, no. 1, hlm. 46, 1964, doi: 10.37358/Mat.Plust.1964.
- [25] J. Christie dan I. G. Platt, *Proceedings : 2014 IEEE Sensors Applications Symposium : February 18-20, 2014, Rydges Lakeland Resort, Queenstown, New Zealand*. IEEE, 2014.
- [26] C. J. Geankoplis, “Transport Processes and Unit Operations,” 1985.
- [27] O. Carol, “Title: A Literature Review on the Study of Moisture in Polymers,” 2016.

- [28] A. S. Mujumdar dan S. Devahastin, "FUNDAMENTAL PRINCIPLES OF DRYING," 2000.
- [29] A. Anthony A, "Theoretical Analysis of Mass and Heat Transfer through a Dehumidifying Plastic Dryer," *International Journal of Engineering Trends and Technology*, vol. 61, no. 2, hlm. 106–115, Jul 2018, doi: 10.14445/22315381/IJETT-V61P218.
- [30] A. S. Mujumdar, "Handbook of Industrial Drying," 2006.
- [31] A. V. Shenoy dan D. R. Saini, "Melt flow index: More than just a quality control rheological parameter. Part I," *Advances in Polymer Technology*, vol. 6, no. 1, hlm. 1–58, 1986, doi: 10.1002/adv.1986.060060101.
- [32] A. V Shenoy, S. Chattopadhyay, dan V. M. Nadkarni, "From melt flow index to rheogram*)," 1983.
- [33] Z. Kalkan -Sevinc Becton, "Moisture Effect on Melt Rheology of Copolyester Blend with Thermoplastic Polyester Elastomer (TPE)," 2016. [Daring]. Tersedia pada:
<https://www.researchgate.net/publication/305699912>
- [34] J. Andrzejewski, W. Gośławska, M. Salamaga, W. Zgoła, dan M. Barczewski, "The Use of the Overmolding Technique for the Preparation of Basalt Fiber (BF)-Based Composite, the Comparative Study of Poly(ethylene terephthalate)/Polycarbonate—PET/PC and Poly(butylene terephthalate)—PBT/PC Blends," *Polymers (Basel)*., vol. 18, no. 1, Jan 2026, doi: 10.3390/polym18010054.
- [35] G. M. Park, J. M. Lee, J. Lee, dan J. W. Wee, "Hygrothermal degradation of short-glass-fiber reinforced polycarbonate: effect of fiber content and orientation, and modeling," *Npj Mater. Degrad.*, vol. 10, no. 1, Des 2026, doi: 10.1038/s41529-026-00774-z.
- [36] S. Bommakanti, S. Rout, J. Mohapatra, S. Nath, dan B. P. Biswal, "Polymer Chemistry: An Overview," 2023. [Daring]. Tersedia pada:
<http://books.rsc.org/books/edited-volume/chapter-pdf/1800727/bk9781839169656-00001.pdf>