

DAFTAR PUSTAKA

- [1] I. Maia, J. Santos, M. J. Abreu, T. Miranda, N. Carneiro, and G. M. B. Soares, "PVC-based synthetic leather to provide more comfortable and sustainable vehicles," *IOP Conf Ser Mater Sci Eng*, vol. 254, no. 12, pp. 8–14, 2017, doi: 10.1088/1757-899X/254/12/122006.
- [2] K. Heinzl, G. T. Gresser, M. Franz, and S. Eiler, "Climate comfort of surface materials for automotive seats," *ATZ worldwide*, vol. 120, no. 2, pp. 68–72, 2018, doi: 10.1007/s38311-017-0178-x.
- [3] V. Naik, M. Kumar, and V. Kaup, "A Review on Natural Fiber Composite Materials in Automotive Applications," *Engineered Science*, vol. 18, pp. 1–10, 2022, doi: 10.30919/es8d589.
- [4] R. Ramasubbu and S. Madasamy, "Fabrication of Automobile Component Using Hybrid Natural Fiber Reinforced Polymer Composite," *Journal of Natural Fibers*, vol. 19, no. 2, pp. 736–746, 2022, doi: 10.1080/15440478.2020.1761927.
- [5] N. Fantuzzi, M. Baccocchi, D. Benedetti, and J. Agnelli, "The use of sustainable composites for the manufacturing of electric cars," *Composites Part C: Open Access*, vol. 4, no. December 2020, p. 100096, 2021, doi: 10.1016/j.jcomc.2020.100096.
- [6] Muh. W. Syabani, C. Devi, I. Hermiyati, and A. D. Angkasa, "The effect of PVC's resin K-value on the mechanical properties of the artificial leather," *Majalah Kulit, Karet, dan Plastik*, vol. 35, no. 2, p. 75, 2020, doi: 10.20543/mkcp.v35i2.5639.
- [7] D. Gurera and B. Bhushan, "SC," *Colloids Surf A Physicochem Eng Asp*, 2018, doi: 10.1016/j.colsurfa.2018.02.052.
- [8] Badan Pusat Statistika, "Impor Komoditi Bahan Perusak Lapisan Ozon (ton), 2000-2016," 2017. <https://www.bps.go.id/statictable/2014/04/28/1352/impor-komoditi-bahan-perusak-lapisan-ozon-ton-2000-2016.html>
- [9] I. A. Altindag and Y. Akdogan, "Spectrophotometric characterization of plasticizer migration in poly(vinyl chloride)-based artificial leather," *Mater Chem Phys*, vol. 258, no. September 2020, p. 123954, 2021, doi: 10.1016/j.matchemphys.2020.123954.
- [10] D. G. H. Adoe, Y. M. Pell, P. Studi, and T. Mesin, "Analisis Pengaruh Perlakuan Alkali Terhadap Wettability Serat Tunggal Widuri," vol. 08, no. 02, pp. 23–28, 2021.
- [11] M. Sholeh and S. Rochani, "Effect of Dioctyl Phtalate Plasticizer On Physical and Mechanical Properties of Synthetic Leather," *Jurnal Litbang Industri*, vol. 8, no. 1, pp. 17–22, 2018.
- [12] E. Oktariani and A. Rakhma, "Pemanfaatan Limbah Polyester Staple Fiber (PSF) dan Polyester Suction Waste (PSW) sebagai Pengisi pada Kulit Sintetis Berbasis Polivinil Klorida

- (PVC),” *Jurnal Teknik Kimia*, vol. 26, no. 3, pp. 103–107, 2020.
- [13] E. Sukardan, M. D., Natawijaya, D., Prettyanti, P., Cahyadi, C., & Novarini, “Karakterisasi Serat Dari Tanaman Biduri (*Calotropis Gigantea*) Dan Identifikasi Kemungkinan Pemanfaatannya Sebagai Serat Tekstil,” *Arena Tekstil*, vol. 2, no. 31, pp. 51–62, 2017.
- [14] M. Rusdan, “Pengembangan Aplikasi Standar Produksi Dan Pemakaian Bahan Pada Perusahaan Kulit Imitasi Berbasis Website,” *Jurnal Ilmiah Teknologi Infomasi Terapan*, vol. 6, no. 2, pp. 79–86, 2020, doi: 10.33197/jitter.vol6.iss2.2020.360.
- [15] Y. K. Afandi and I. S. Arief, “Analisa Laju Korosi pada Pelat Baja Karbon dengan Variasi Ketebalan Coating,” vol. 4, no. 1, pp. 1–5, 2017.
- [16] Z. Alam, “Evaluasi Sifat Mekanik,” vol. 18, no. 235, pp. 18–35, 2018.
- [17] R. F. Gibson, *Principles of Composite Material Mechanics*. Singapore: McGraw-Hill, 1994.
- [18] S. Y. Fu, G. Xu, and Y. W. Mai, “On the elastic modulus of hybrid particle/short-fiber/polymer composites,” *Composites Part B:Engineering*, vol. 33, no. 4, pp. 291–299, 2002, doi: 10.1016/S1359-8368(02)00013-6.
- [19] T. Addriyanus, “Pengaruh Komposisi dan Ukuran Makro Serbuk Kulit Kerang Darah (*Anadora Granosa*) Terhadap Komposit Epoksi-PS/Serbuk Kulit Kerang Darah (SKKD),” Universitas Sumatra Utara, 2015.
- [20] R. A. W. Mines, A. M. Roach, and N. Jones, “High velocity perforation behaviour of polymer composite laminates,” *Int J Impact Eng*, vol. 22, no. 6, pp. 561–588, 1999, doi: 10.1016/S0734-743X(99)00019-6.
- [21] C. A. Harper, *Modern Plastics Handbook*. USA: McGraw-Hill, 1999.
- [22] D. K. Akovali, G. Banerjee, B., Sen, A.K., Setua, *Advances In Polymer Coated Textiles*. Smithers Rapra, 2012.
- [23] J. R. Fried, *Polymer Science And Technology*. USA: Prentice Hall College, 1995.
- [24] A. I. Al-mosawi, K. Marossy, and C. Kónya, “Effect of Plasticizer Percentage on Thermal Properties of Plasticised PVC,” vol. 117, no. June, pp. 50509–50511, 2018, doi: 10.6084/m9.figshare.12567878.
- [25] A. G. Aditama and H. Ardhyanta, “Isolasi Selulosa dari Serat Tandan Kosong Kelapa Sawit untuk Nano Filler Komposit Absorpsi Suara: Analisis FTIR,” *Jurnal Teknik ITS*, vol. 6, no. 2, pp. 228–231, 2017, doi: 10.12962/j23373539.v6i2.24098.
- [26] P. Narayanasamy *et al.*, “Characterization of a novel natural cellulosic fiber from *Calotropis gigantea* fruit bunch for ecofriendly polymer composites,” *Int J Biol Macromol*, vol. 150, pp. 793–801, 2020, doi: 10.1016/j.ijbiomac.2020.02.134.
- [27] Z. Ashori, A; Bahreini, “Evaluation of *Calotropis gigantea* as a Promising Raw Material for

- Fiber-reinforced Composite,” *J Compos Mater*, 2009.
- [28] K. Chandramohan, D. ; Marimuthu, “A REVIEW ON NATURAL FIBERS,” *IJRRAS*, vol. 8, no. 2, pp. 194–206, 2011, doi: 10.1089/aid.1996.12.1427.
- [29] M. A. Pradana, H. Ardhyanta, and M. Farid, “Pemisahan Selulosa dari Lignin Serat Tandan Kosong Kelapa Sawit dengan Proses Alkalisasi untuk Penguat Bahan Komposit Penyerap Suara,” *Jurnal Teknik ITS*, vol. 6, no. 2, pp. 413–416, 2017, doi: 10.12962/j23373539.v6i2.24559.
- [30] B. Fotovvati, N. Namdari, and A. Dehghanghadikolaei, “On coating techniques for surface protection: A review,” *Journal of Manufacturing and Materials Processing*, vol. 3, no. 1, 2019, doi: 10.3390/jmmp3010028.
- [31] G. Wypych, *Handbook of Plasticizer*. New York: Chemtech, 2004.
- [32] M. H. Effendi, “Modifikasi dan Penggunaan Pemlastis Turunan Asam Oleat pada Matriks Polivinil Klorida,” Universitas Sumatera Utara, Medan, 2000.
- [33] F. M. Herman, *Encyclopedia of Polymer Science and Technology*, 3rd ed. New Jersey: John Wiley and Sons, 2007.
- [34] W. S. Wilkes, Charles E; Charles, A Daniels; James, *PVC Handbook*. Hanser, 2005.
- [35] J. Murphy, *Additives for Plastics*, 2nd ed. Oxford: Elsevier Science Ltd., 2001.
- [36] T. A. O. and N. R. Erwin Baur, *Plastics Handbook: The Resource for Plastics Engineers*. Munich: Carl Hanser Verlag, 2018. doi: <https://doi.org/10.3139/9781569905609>.
- [37] and S. Sunarso, Hs, S Rochani, Supraptingsih, Sofyan Karani, H Surip, “Penelitian Pengaruh Stabilizer BaCd Kompleks Terhadap Sifat Fisis Kompon PVC Untuk Acuan Sepatu,” *Majalah Kulit, Karet, dan Plastik* 2, 1986.
- [38] E. D. Owen, *Degradation and Stabilisation of PVC*. Elsevier Applied Science, 1984.
- [39] B. S. Sudirman, Aloma Karo Karo, Ari H, “Analisis Sifat Kekuatan Tarik, Derajat Kristalinitas dan Strukturmikro Komposit Polimer Polipropilena- Pasir,” *Jurnal Sains Materi Indonesia*, vol. 1, no. 6, pp. 1–6, 2004.
- [40] and A. M. Setiabudi, A, R Hardian, *Karakterisasi Material: Prinsip dan Aplikasinya dalam Penelitian Kimia*. Bandung: Universitas Pendidikan Indonesia, 2012.
- [41] W. L. Hawkins, *Polymer Degradation and Stabilization. Polymers Properties and Applications* 8. New York: Springer-Verlag, 1984.
- [42] Y. Ma, X. Dang, and Z. Shan, “Thermal Analysis and Identification of Potential Fire-proof Energy Building Material Based on Artificial Leather,” *Journal of Thermal Science*, vol. 28, no. 1, pp. 88–96, 2019, doi: 10.1007/s11630-018-1054-8.
- [43] F. Wang, S. Pan, P. Zhang, H. Fan, Y. Chen, and J. Yan, “Synthesis and Application of

Phosphorus-containing Flame Retardant Plasticizer for Polyvinyl Chloride,” *Fibers and Polymers*, vol. 19, no. 5, pp. 1057–1063, 2018, doi: 10.1007/s12221-018-7493-8.

- [44] K. Renugadevi, P. K. Devan, M. Chandra Sekhara Reddy, P. Karthik, and T. Thomas, “Optimization of surface treatment in Calotropis Gigantea (CG)-fibre yarn by simple techniques and characterization of CG fibre yarn reinforced laminate,” *Journal of Materials Research and Technology*, vol. 9, no. 6, pp. 12187–12200, 2020, doi: 10.1016/j.jmrt.2020.08.058.
- [45] I. Kurniaty, “Proses Delignifikasi Menggunakan Naoh Dan Amonia (Nh3) Pada Tempurung Kelapa,” *Jurnal Integrasi Proses*, vol. 6, no. 4, p. 197, 2017, doi: 10.36055/jip.v6i4.2546.
- [46] P. Ganeshan, B. NagarajaGanesh, P. Ramshankar, and K. Raja, “Calotropis gigantea fibers: A potential reinforcement for polymer matrices,” *International Journal of Polymer Analysis and Characterization*, vol. 23, no. 3, pp. 271–277, 2018, doi: 10.1080/1023666X.2018.1439560.