

## DAFTAR PUSTAKA

- [1] J. P. Jose, S. K. Malhotra, S. Thomas, K. Joseph, K. Goda, dan M. S. Sreekala, “Advances in polymer composites: Biocomposites-state of the art, new challenges, and opportunities,” in *Polymer Composites, Biocomposites*, 2013, hal. 1–10. doi: 10.1002/9783527674220.ch1.
- [2] A. S. Utama, P. Kurniawan, A. Nugroho, dan W. S. Hayu, “Studi Pemanfaatan Limbah Material Polypropilene (PP) untuk Pembuatan Produk Cone Benang dengan Penambah Material Kalsium Karbonat,” *J. Rekayasa Sist. Ind.*, vol. 11, no. 1, hal. 101–108, 2022, doi: 10.26593/jrsi.v11i1.5288.101-108.
- [3] R. Purnawati, F. Febrianto, N. J. Wistara, S. Nikmatin, Sudirman, dan Marwanto, “Aplikasi Serat Kapuk dan Balsa dengan Perlakuan Alkali sebagai Bahan Penguat Komposit ( Alkaline Treated-Kapok and Balsa Fibers for Composite Reinforcement ),” *J. Ilmu Teknol. Kayu Trop.*, vol. 16, hal. 23–33, 2018.
- [4] D. Kumar, A. Srivastav, dan V. Gautam, “Investigation on mechanical and thermo-mechanical properties of injection molded PP-TiO<sub>2</sub>composites,” *Mater. Today Proc.*, vol. 44, hal. 4607–4611, 2020, doi: 10.1016/j.matpr.2020.10.912.
- [5] A. Achmadi, “Pengaruh Perlakuan Quenching Dengan Variasi Pendingin Konsentrasi Air Garam Terhadap Kekerasan Dan Kekuatan Tarik Pada Baja St 37,” *Simetris*, vol. 11, no. 2, hal. 34–42, 2017.
- [6] J. C. Williams dan E. A. Starke, “Progress in structural materials for aerospace systems,” *Acta Mater.*, vol. 51, no. 19, hal. 5775–5799, 2003, doi: 10.1016/j.actamat.2003.08.023.
- [7] N. H. Sari, *Teknologi Papan Komposit Diperkuat Serat Kulit Jagung*. Yogyakarta: Deepublish, 2019.
- [8] Sudirman, K. K. Aloma, I. Gunawan, A. Handayani, dan E. Hertinvyana, “Synthesis And Characterization Of Polypropylene/Jigsaw Wood Ash Composite,” *J. Sains Mater. Indones.*, vol. 4, no. 1, hal. 20–25, 2002.
- [9] D. V Rosanto, D. V Rosanto, dan M. G. Rosanto, *Injection Molding Handbook*, 3 ed. Kluwer Academic, 2000.
- [10] Irwanto, “Pemanfaatan serat kulit jagung (zea mays) sebagai camputan gipsum untuk pembuatan plafon degan bahan pengikat resin epoksi,” Universitas Sumatera Utara, 2018.

- [11] H. Zhang, J. Wang, G. Xu, Y. Xu, F. Wang, dan H. Shen, "Ultralight, hydrophobic, sustainable, cost-effective and floating kapok/microfibrillated cellulose aerogels as speedy and recyclable oil superabsorbents," *J. Hazard. Mater.*, vol. 406, hal. 124758, 2021, doi: 10.1016/j.jhazmat.2020.124758.
- [12] D. Ciechańska, E. Wesolowska, dan D. Wawro, "An introduction to cellulosic fibres," *Handb. Text. Fibre Struct.*, vol. 2, hal. 3–61, 2009, doi: 10.1533/9781845697310.1.3.
- [13] F. Parrino, F. R. Pomilla, G. C. Roda, V. Loddo, dan L. Palmisano, *Titanium Dioxide (TiO<sub>2</sub>) and Its Applications*. Matthew Dean, 2021. doi: 10.1016/b978-0-12-819960-2.00024-9.
- [14] B. Maryanti, A. A. Sonief, dan S. Wahyudi, "Pengaruh Alkalisasi Komposit Serat Kelapa-Poliester Terhadap Kekuatan Tarik," *Rekayasa Mesin*, vol. 2, no. 2, hal. 123–129, 2011.
- [15] I. Gunawan, B. Sugeng, K. K. Aloma, dan D. Chrissanti, "Pengaruh Quenching Pada Polietilena Dan Polipropilena," *J. Sains Mater. Indones.*, vol. 7, hal. 25–31, 2006.
- [16] N. Uthaipan, M. Jarnthong, Z. Peng, B. Junhasavasdikul, C. Nakason, dan A. Thitithammawong, "Effects of cooling rates on crystallization behavior and melting characteristics of isotactic polypropylene as neat and in the TPVs EPDM/PP and EOC/PP," *Polym. Test.*, vol. 44, hal. 101–111, 2015, doi: 10.1016/j.polymertesting.2015.04.002.
- [17] B. Lu, Y. Yakushi, Y. Oumi, K. Itabashi, dan T. Sano, "Control of crystal size of high-silica mordenite by quenching in the course of crystallization process," *Microporous Mesoporous Mater.*, vol. 95, no. 1–3, hal. 141–145, 2006, doi: 10.1016/j.micromeso.2006.05.017.
- [18] M. Fahrurrozi, B. Senowulung, dan Moristanto, "Pengaruh Kecepatan Pendinginan Terhadap Perubahan Volume Leburan Polymer Crystalline dan Non-Crystalline," *Forum Tek.*, vol. 27, no. 3, hal. 132–139, 2003.
- [19] S.-J. Liu, *Injection molding in polymer matrix composites*. Woodhead Publishing Limited, 2012. doi: 10.1533/9780857096258.1.13.
- [20] S. Ahsan, "Spektrum Inframerah dan Sifat Termal Poliasam Laktat (PLA): Perbandingan Filler Seng Oksida dan Kalsium Karbonat," *J. Teknol. dan Manaj.*, vol. 18, no. 2, hal. 40–50, 2020.
- [21] X. Zheng, T. Yang, J. Wei, C. Wang, dan M. Chen, "Co-contribution of quenching and nanocrystallization on ionic-conductivity improvement of a composite electrolyte of polyethylene Oxide/Li<sub>7</sub>La<sub>3</sub>Zr<sub>2</sub>O<sub>12</sub> nanofibers at 45 °C for all-solid-state Li metal batteries," *J. Power Sources*, vol. 496, no. MarchGunawan, I., Handayani, A., Hertinvyana, E., Dan, S., Komposit, K., Serbuk, P., Gergaji, K., Kerja, C. (2002). Synthesis And Characterization Of Polypropylene/Jigsaw Wood Ash Composite. *Jurnal Sains Materi Indonesia*, 4(1), 20–25., 2021, doi: 10.1016/j.jpowsour.2021.229843.