

DAFTAR PUSTAKA

- [1] H. M. R. H. Subawi, “Pengenalan Teknik Komposit,” *Deepublish*, 2016.
- [2] G. D. Domingo dan A. M. C. Souza, “PA6/PA66/talc composite: Effect of reprocessing on the structure and properties,” *J. Appl. Polym. Sci.*, vol. 139, no. 13, hal. 1–9, 2022, doi: 10.1002/app.51869.
- [3] G. Colucci, O. Ostrovskaya, A. Frache, B. Martorana, dan C. Badini, “The effect of mechanical recycling on the microstructure and properties of PA66 composites reinforced with carbon fibers,” *J. Appl. Polym. Sci.*, vol. 132, no. 29, hal. 1–9, 2015, doi: 10.1002/app.42275.
- [4] N. Safriani, E. Kurniawan, dan S. Bahri, “Pembuatan Komposit Hybrid Dari serbuk Bentonit dan Pelepas Pisang dengan penguat matrik Polyesterena,” vol. 2, no. Oktober, hal. 35–45, 2021.
- [5] V. De Oliveira, S. Neto, dan G. D. Saraiva, “Hybrid polymers composite: effect of hybridization on the some propsers of the materials 11,” 2017, doi: 10.1016/B978-0-08-100791-4.00011-2.
- [6] S. N. Maiti dan B. H. Lopez, “Tensile properties of polypropylene/kaolin composites,” *J. Appl. Polym. Sci.*, vol. 44, no. 2, hal. 353–360, 1992, doi: 10.1002/app.1992.070440219.
- [7] N. Phutfak dan A. Larpkasemsuk, “Wollastonite and talc reinforced polypropylene hybrid composites: Mechanical, morphological and thermal properties,” *J. Met. Mater. Miner.*, vol. 31, no. 3, hal. 92–99, 2021, doi: 10.14456/jmmm.2021.43.
- [8] E. Sasimowski, Ł. Majewski, dan M. Grochowicz, “Influence of the conditions of corotating twin-screw extrusion for talc-filled polypropylene on selected properties of the extrudate,” *Polymers (Basel)*., vol. 11, no. 9, 2019, doi: 10.3390/polym11091460.
- [9] M. Kodal, S. Erturk, S. Sanli, dan G. Ozkoc, “Properties of Talc/Wollastonite/Polyamide 6 Hybrid Composites,” *Polym. Polym. Compos.*, vol. 16, no. 2, hal. 1–8, 2015, doi: 10.1002/polym.201500002.
- [10] Barleany Dhena Ria, Rudi Hartono, dan Santoso, “Pengaruh Komposisi Montmorillonite pada Pembuatan Polipropilen- Nanokomposit terhadap Kekuatan Tarik dan Kekerasannya,” *Teknol. Kim.*, hal. 1–6, 2011.
- [11] O. V. Alekseeva, A. N. Rodionova, N. A. Bagrovskaya, A. V. Noskov, dan A. V. Agafonov, “Bentonite filler effect on structure and properties of polystyrene-based composites,” *Iran. Polym. J. (English Ed.)*, vol. 28, no. 2, hal. 123–133, 2019, doi: 10.1007/s13726-018-0683-9.
- [12] A. O. Akar, U. H. Yildiz, dan U. Tayfun, “Investigations of polyamide nano-composites containing bentonite and organo-modified clays: Mechanical, thermal, structural and processing performances,” *Rev. Adv. Mater. Sci.*, vol. 60, no. 1, hal. 293–302, 2021, doi:

10.1515/rams-2021-0025.

- [13] M. Yani, "Kekuatan Komposit Polymeric Foam Diperkuat Serat Tandan Kosong Kelapa Sawit Pada Pembebasan Dinamik," *J. Mek.*, vol. 4, no. 2, hal. 67–76, 2016.
- [14] F. I. Aryanti, "Pembuatan Komposit Polimer Polipropilena/Talk/Masterbatch Hitam Pada Cover Tail," *J. Teknol. dan Manaj.*, vol. 19, no. 1, hal. 1–6, 2021, doi: 10.52330/jtm.v19i1.8.
- [15] A. Teknologi.com, "Pengertian Material Komposit," *Artikel Teknologi.com*, 2023.
- [16] T. dkk Sabu, *Polymer Composites*, 1 ed. Wiley-VCHVerlag GmbH & Co.KGaA, 2012. doi: 10.1016/B978-0-12-821984-3.00003-6.
- [17] W. D. Callister dan J. Wiley, *Materials Science and Engineering*, 7 ed. USA: John Wiley & Sons.Inc, 2007.
- [18] M. A. Ihsan, "Studi Pengaruh Komposisi Filler Batu Alam dan Limbah Melamin Terhadap Sifat Mekanik dan Sifat Fisis Material Komposit Epoksi/Melamin/Batu Alam Untuk Aplikasi Tile," *Dep. Tek. Mater. Fak. Teknol. Ind. ITS Surabaya*, hal. 1–103, 2018.
- [19] R. M. Jones, *Mechanics of Composite Materials*, Second. Taylor & Francis 1798, 1999.
- [20] C. Saravanan, K. Subramanian, K. V. A. Krishnan, dan R. Sankara Narayanan, "Effect of Particulate Reinforced Aluminium Metal Matrix Composite-A Review," *Mech. Mech. Eng.*, vol. 19, no. 1, hal. 23–30, 2015.
- [21] K. K. Chawla, *Composite Materials: Science and Engineering*. 2019.
- [22] M. Sanjay, *Composites Manufacturing Materials, Product, and Process Engineering*. Boca Raton London New York Washington, D.C.: CRC PRESS, 2002.
- [23] H. S. Nasmi, *Teknologi Papan Komposit Diperkuat Serat Kulit Jagung*. Deepublish, 2019.
- [24] T. Puwarto, "Pembuatan Produk Berbahan Komposit Serat Bambu Apus Studi Kasus Aksesoris Interior Mobil Dengan Bentuk Dan Kontur Lengkung Yang Sederhana," hal. 4–12, 2019.
- [25] F. C. Campbell, *Structural Composite Materials*. 2010. doi: 10.31399/asm.tb.scm.9781627083140.
- [26] M. V. Fernández *et al.*, "Effect of Nanometric Particles of Bentonite on the Mechanical Properties of a Thermoset Polymeric Matrix Reinforced with Hemp Fibers," *Polymers (Basel)*., vol. 15, no. 6, 2023, doi: 10.3390/polym15061571.
- [27] L. . McKeen, *Polyamides (Nylons)*, Fourth. 2019. doi: 10.1016/B978-0-12-816457-0.00007-1.
- [28] M. Gilbert, *Brydson's Plastics Materials*, Eight th. Butterworth-Heinemann is an imprint of Elsevier, 2017.
- [29] C. A. Harper, *Handbook Modern Plastics*. McGraw-Hill, 2000.

- [30] T. Surdia, *Teknik Pengetahuan Bahan*. Jakarta: PT. Pradnya Paramita, 1999.
- [31] G. Wypych, “HANDBOOK OF POLYMERS Pa-6,” *Pa-6,6*, hal. 215–220, 2012, doi: 10.1016/B978-1-895198-47-8.50070-9.
- [32] G. Wypych, *Handbook of Fillers*. 2016. doi: 10.1108/prt.1999.12928bae.002.
- [33] Castillo, “Influence of Talc Genesis and Particle Surface on the Crystallization Kinetics of Polypropylene/Talc Composites,” *J. Appl. Polym. Sci.*, hal. 1–10, 2012, doi: 10.1002/app.
- [34] P. C. De Carvalho Pinto, V. R. Da Silva, M. I. Yoshida, dan M. A. L. De Oliveira, “Synthesis of flexible polyurethane foams by the partial substitution of polyol by steatite,” *Polimeros*, vol. 28, no. 4, hal. 323–331, 2018, doi: 10.1590/0104-1428.10417.
- [35] N. Martín dan F. Giacalone, *Fullerene Polymers: Synthesis, Properties and Applications*. 2009. doi: 10.1002/9783527628742.
- [36] V. Egypt, “High quality fine talc powder pure white talcum 325 mesh,” 2018.
- [37] W. Colloids, *Wine Colloids*. 2012. doi: 10.1016/b978-0-12-388438-1.00019-4.
- [38] D. Price, “Structure Of Illite,” *Rig Worker*, 2023.
- [39] H. H. Murray, “Developments in Clay Science Applied Clay Mineralogy - Occurrences, Processing and Application of Kaolins, Bentonites, Palygorskite-Sepiolite, and Common Clays,” *chapter 6 Bentonite Applications*, vol. 2, hal. 111–130, 2006.
- [40] F. Korkees, A. Aldrees, I. Barsoum, dan D. Alshammari, “Functionalised graphene effect on the mechanical and thermal properties of recycled PA6/PA6,6 blends,” *J. Compos. Mater.*, vol. 55, no. 16, hal. 2211–2224, 2021, doi: 10.1177/0021998320987897.
- [41] D. S. Choudhari dan V. J. Kakhandki, “Comprehensive study and analysis of mechanical properties of chopped carbon fibre reinforced nylon 66 composite materials,” *Mater. Today Proc.*, vol. 44, no. xxxx, hal. 4596–4601, 2020, doi: 10.1016/j.matpr.2020.10.828.
- [42] R. H. Setyanto, “Review : Teknik Manufaktur Komposit Hijau dan Aplikasinya,” *Performa*, vol. 11, no. 1, hal. 9–18, 2012.
- [43] Alatuji, “QC-601A Manual Thermos Press Forming Machine,” vol. 6777, no. 62. hal. 21–22, 2023.
- [44] A. A. Shamsuri, “Compression Moulding Technique for Manufacturing Biocomposite Products,” *Int. J. Appl. Sci. Technol.*, vol. 5, no. 3, hal. 23–26, 2015.
- [45] G. Kiran, K. Suman, N. Rao, dan R. Rao, “A study on the influence of hot press forming process parameters on mechanical properties of green composites using Taguchi experimental design,” *Int. J. Eng. Sci. Technol.*, vol. 3, no. 4, hal. 253–263, 2011, doi: 10.4314/ijest.v3i4.68557.

- [46] American Society for Testing and Materials, “ASTM D638-14, Standard Practice for Preparation of Metallographic Specimens,” *ASTM Int.*, vol. 82, no. C, hal. 1–15, 2016, doi: 10.1520/D0638-14.1.
- [47] Y. M. P. Harun N. Beliu, “Analisa Kekuatan Tarik dan Bending pada Komposit Widuri - Polyester,” *Lontar Tek. Mesin Undana*, vol. 03, no. 02, hal. 11–20, 2016.
- [48] Z. Achmad, “Kekakuan Bending Ekperimen Komposit Sandwich Serat Sabut Kelapa Matrik Poliester Dengan Core Kertas Kardus,” *Jur. Tek. Mesin Fak. Tek. Univ. Mataram*, 2011.
- [49] M. Sajid dan H. Akash, *Essentials of Pharmaceutical Analysis*. Singapore: Springer Nature Singapore Pte Ltd. 2020, 2020.
- [50] A. Setiabudi, R. Hardian, dan A. Muzakir, *Karakterisasi Material: Prinsip dan Aplikasinya dalam Penelitian Kimia*, vol. 1. 2012.
- [51] P. Mokhtar, “Kurva DSC,” *Slideshare*. 2014.
- [52] B. Krause, L. Kroschwitzl, dan P. Pötschke, “The influence of the blend ratio in PA6/PA66/MWCNT blend composites on the electrical and thermal properties,” *Polymers (Basel)*., vol. 11, no. 1, 2019, doi: 10.3390/polym11010122.
- [53] E. Melyna, K. S. Nisa, A. Aurel, dan L. Fitri, “Pengaruh penambahan serbuk alumina (Al 2 O 3) pada komposit serat kayu jati bermatriks polipropilena The effect of alumina (Al 2 O 3) addition on teak powder and polypropylene composite Received February 2023 , Revised May 2023 , Accepted for publicat,” vol. 29, no. 2, hal. 62–70, 2023.
- [54] E. Riande, *Polimer Viscoelasticity Stress and Strain In Practice*. USA: Marcell Dekker Inc, 2000.